



Personal Monitor

For oxygen, toxic
or flammable gases

Gasman **A personal monitor you can trust**

Designed to meet the need for personal monitoring in tough industrial environments, Gasman is small, light, and simple to use providing comprehensive warning of hazardous gas conditions.

Featuring interchangeable i-module intelligent sensors and simple single button operation Gasman is the most flexible and easy to use product available today.

Rugged in design meeting both IP65 and IP67 standards for ingress protection, Gasman sets a new standard for personal gas monitors.

Simple

- True one button operation
- Easy to read LCD display with backlight
- Clear indication of operating status
- 30 days advance calibration due warning

Assurance

- 95dBA audible alarm
- Striking twin red/blue visual alarm
- Internal vibrating alarm
- 2 levels of instantaneous alarm
- Time weighted average alarms for toxic versions

Robust

- Tough polycarbonate housing
- Full elastomeric overmoulding
- High impact resistance
- IP65 and IP67 compliant

Flexible

- Fully interchangeable i-module sensors
- Flammable toxic and oxygen sensors available
- Rechargeable version for all gas types
- Dry cell versions for toxics and oxygen
- Data and event logging

Specification

Weight	130g flammable 100g oxygen 90g toxic		
Dimensions	90x48x24mm (3.5x1.9x0.95 inch) HxWxD		
Available gases and ranges			
Gas	Range	Alarm UK and ROW	Alarm US
Flammable	0-100%LEL	20%LEL	10%LEL
Oxygen	0-25%	19/23.5%	19.5/23.5%
Hydrogen Sulphide	0-50ppm	5ppm	10ppm
Carbon Monoxide	0-500ppm	30ppm	35ppm
Sulphur Dioxide	0-10ppm	1ppm	2ppm
Chlorine	0-5ppm	0.5ppm	0.5ppm
Nitrogen Dioxide	0-10ppm	1ppm	3ppm
Ammonia	0-50ppm	25ppm	25ppm
Ozone	0-1ppm	0.1ppm	0.1ppm
Hydrogen	0-1000ppm	N/A	N/A
Hydrogen Cyanide	0-25ppm	5ppm	5ppm
Hydrogen Chloride	0-10ppm	1ppm	1ppm
Hydrogen Fluoride	0-10ppm	1ppm	1ppm
Phosphine	0-2ppm	0.2ppm	0.2ppm
Ethylene Oxide	0-10ppm	5ppm	5ppm
Other ranges and alarm levels are available on request. Each unit can have two instantaneous alarm levels set. Toxic units also have Time Weighted Average alarms.			
Flammable gas calibration is available for methane, propane, butane, pentane, hydrogen and ethylene as standard.			
Typical response times	Flammable 20s, Toxic gas 20s, Oxygen 10s		
Audible Alarms	95dBA Multiple alarm sounds allow selection of distinctive tones for different alarm levels		
Visible Alarms	Dual colour red/blue flashing LEDs in gas hazard		
Vibrating alarm	Internal vibrating alarm		
Display	Custom LCD with backlight, with display of gas concentration. Graphic symbols for battery (with proportional indication of remaining operation time), and display mode. Start up indication when calibration is due within 30 days, calibration overdue, or service required.		
Display Mode	Normal display for real time gas concentration levels. Display recall for Peak readings and TWA		
Datalogging	Full timed datalogging with adjustable sample rate, set to 1 minute data rate. 900 hours storage at 1 minute interval. 5000+ capacity event logging to record all instrument events including: Switch on/off, Battery status, Alarms activate/clear including peak values of response, Gas Test pass or fail. All events are time stamped		

Battery Types	Rechargeable Li-ion battery Non rechargeable Lithium Cell
Operating Time	Rechargeable: 12 hours minimum for flammable unit Non rechargeable: Up to 2 years
Note: Operating time will depend on operating pattern and alarm occurrence. Frequent or long lasting alarms and use of the optional confidence beep will reduce battery life.	
Sampling	Optional manual aspirator
Operating temp. range	-20°C to +55°C (-4°F to +131°F)
Humidity	0-99% RH
Approval Codes	
Europe:	ATEX II 1G EEx ia IIC T4 (Tamb -20°C to +55°C) Toxic/Oxygen ATEX II 2G EEx iad IIC T4 (Tamb -20°C to +55°C) Flammable
USA/Canada	Class I Groups A, B, C, D Division I
Standards	
Safety	
Europe	EN50014, EN50020, EN50018, 94/9/EC
USA & Canada	UL913, CSA22.2, 152
Operation	EN50270, EN50271, EN61779 Software designed to meet IEC61508
Ingress Protection	IP65/IP67
PC Interface	RS232 connection from Interface module in charger. RS232/USB convertor available
Autocalibrator	Gasman can be routinely calibrated using the Crowcon Autocalibrator II in conjunction with the PC software.
Accessories	Gasman is supplied with an integral pocket clip.
Charger	Single way drop in charger with options of UK, European or US style plug in mains supplies, or in line universal supply. Optional PC interface module within the single way charger. Vehicle lighter socket lead available. 5 way multicharger with universal power supply.
Optional accessories include: alligator clip, universal harness plate, shoulder strap, chest harness, aspirator assembly (flow plate, bulb and 2m/6ft tubing).	